


198.95 EUR

incl. 19% VAT, plus [shipping](#)

- Intel Bay Trail !
- 4x2.42Ghz CPU !
- 2x Gigabit LAN !
- 4x RS232 !



This board is produced by MITAC, the OEM producer of Intel D2500CC. This board is identical with Intel D2500CC (even BIOS-compatible).

This model can be connected directly to a 12V DC power source.

- Successor model of Intel D2500CC-E mainboard
- Quad-core Intel Celeron J1900
- DVI-I for full dual-independent display support
- 4 serial ports & headers for multiple peripherals
- Boards are suitable for other devices; ATM, Kiosk, POS, etc.

Name	Mitac PD11BI-PSU (Intel D2500CC2)
Form Factor	Mini-ITX Mainboard
CPU	Intel® Celeron™ J1900 (4x 2.42GHz) 2MB Cache, VT-x/Intel64-compatible
Graphics	VGA + DVI-I + LVDS
Memory	2x SO-DDR3L [Low Voltage, 1.35V] 1066/1333, 8GB max, Dual channel
Power	P4 12VDC
LAN	2x Realtek RTL8111G-CG 10/100/1000 MBit
Connectors (rear)	- 2x USB 2.0 - 2x USB 3.0 - 2x LAN RJ-45 - 3x Audio - 2x PS/2 - 2x RS232 - 1x DVI-I - 1x VGA
Audio	6+2 Channel HD Audio
Connectors (internal)	- 2x SATA-II (3GB/s) - 2x USB 2.0 - 1x Intel Z-U130 USB Header - 1x PCIe x1 - 1x Mini-PCIe - 2x RS232 - 1x Parallel LPT - Front Audio - LVDS (Dual 24bit)
Included	- Mitac PD11BI-PSU (D2500CC2) Mainboard (with 4x 2.42Ghz Bay-Trail CPU) - I/O ATX rear plate - SATA power cable - 1x SATA cable