



999.00 EUR
incl. 19% VAT, plus [shipping](#)

- Intel® Apollo Lake N3350/N4200 Processor
- 1 * SO-DIMM Dual CH DDR3L up to 8GB
- 2 * USB3.0, 6 * RJ45, 1 * RS232(RJ45 TYPE)
- M/B Form Factor : Mini ITX (170x170mm)
- 1U FLEX POWER_200W

MB Model	– JNF692G6-335 / JNF692G6-420 (Mini-ITX) – JNF692G6-335B1 / JNF692G6-420B1 (Mini-ITX/1 pair support Bypass LAN)				
Part No	– HBJC153F692-335B – HBJC153F692-420B				
	Bypass LAN	Expansion 4 ports LAN PCI-E Card	Bypass LAN+ Expansion 4 ports LAN PCI-E Card	2 Pairs of Bypass LAN	
	– HBJC153F692B-335B – HBJC153F692B-420B	– HBJC153F692-33G4 – HBJC153F692-42G4	– HBJC153F692B-33G4 – HBJC153F692B-42G4	– HBJC153F692-33B4 – HBJC153F692-42B4	
BIOS	– AMI 128MB SMT Flash ROM				
CPU/Chipset	– INTEL® Apollo Lake N3350/N4200 Processor				
Memory	– 1 * SO-DIMM slots DDR3L-1866MHz up to 8GB				
Storage	– 1 * 2.5" SATA3 6Gb/s internal drive bay – 1 * Full-size mSATA/mini-PCI Express shared slot				
Expansion	– 1 * Full size Mini-PCIE – 1 * SIM Card Slot				
Network	– 6 * Intel i211AT Gigabit LAN – 1 * Full-size mini-PCIE slot (802.11 b/g/n + BT 4.0 installed in WIFI model)				
Rear Panel I/O	– 1 * Power SWITCH – AC INPUT / 1U FLEX 200W Power build in				
Front Panel I/O	– 6 * RJ45 – 2 * USB3.0 – 1 * RS232 (RJ45 TYPE) – 1 * PW LED, 1 * Alarm LED – 1 * HDMI (Not assembled when shipped, wire placed in the parts box) – 1 * GPIO (Not assembled when shipped, wire placed in the parts box) – 2 * COM (optional- RS232/422/485) Expansion 4 ports LAN PCI-E Card: HBJC153F692-33(42)G4 Expansion 2 pairs of Bypass LAN PCI-E Card: HBJC153F692-33(42)B4				

Power Source	- 1U FLEX 200W Power build in - AC 90~240V input
Compliance	- CE, FCC, RoHS
Temperature	- Operating Temperature: 0 ~ 40° C - Storage Temperature: -10 ~ 70° C
Dimensions	- 430 (W) x 252 (D) x 44 (H) mm
Packing	- Net Weight: 4.2KG - Gross Weight: 5KG - Color Box dimension: 560 (W) * 400 (D) * 380 (H) mm
OS Support	- Windows 10, Linux
Warranty	- 2 Year limited warranty